



MODEL: ILOGIC MS PLUS **WATTS** 700W **VOLTAGE:** 100 - 277V SKU IL-L700MS

TECHNICAL SPECS


TECHNICAL SPECS	
Rated Voltage	100 - 277V
Power Consump	$700W \pm 5\%$
Power Supply	Sosen LED Drivers
ePAR - PPF	2298 μmol/s
ePAR Efficacy - Efficacy	$3.04~\mu mol/J$
LED Spectrum	Full Spectrum + UV + IR
Min Power Factor - Power Factor	>0.9
THD	<10%
Crest Factor	<10%
BTU	2300
Frequency	60Hz
Dimming	0 - 100% dimming via RS485
Ambient Temperature - Working	0°C - 35°C / 32° - 95°F
Relative Humidity	<90%
Color Temperature	4000K
Color Rendering Index	85
Emitting Cooling	Aluminum heatsink
Light Distribution - Beam Angle	120 Degree
Waterproof Rating	IP65
LED Lifespan	50000 hours
Daisy Chain	Unlimited with Plus Repeater
Light Source	Samsung LM281B+ Pro * 2184pcs Honglitronic SMD3535 660nm * 168pcs Honglitronic SMD3030 (UV) * 144pcs Honglitronic

SMD2835 (FR) * 144pcs

PHYSICAL SPECIFICATIONS

75 mm/2.9" Height

13.5kg / 15.5kg | 29.7lbs / 34.1lbs Weight - N.W./G.W. Package Size 1130*575*85mm / 44.5* 22.6*3.3"




VOLTAGE AND AMPERAGE


Voltage 120V 208V 220V 240V 277V

Amperage 5.84A 3.37A 3.19A 2.92A 2.53A


SPECTRUM




Full Spectrum 100% ON.




UV 100% ON.




Full Spectrum ON 100% + UV 100% ON.



FR 100% ON.



Full Spectrum 100% ON+ FR 100% ON.



Full Spectrum 100% ON + UV 100% ON + FR 100% ON.



This commercial fixture requires a separately purchased Plus Controller to operate.









MODEL: ILOGIC MS PLUS **VOLTAGE:** 100 - 277V

WATTS 700W SKU IL-L700MS



Why Growers Choose Us

- Designed for multi-tier racking systems.
- Built to last with no need for replacements, with removable bars and driver, zero down time in your facility.
- The first smart fixture ever designed to prevent hermaphroditism or re-vegging.








MODEL: ILOGIC MS PLUS **VOLTAGE:** 100 - 277V


WATTS 700W SKU IL-L700MS

PPFD MAP


Height of 12" / 30CM PAR Distribution



Height of 24" / 60CM PAR Distribution



Height of 31" / 80CM PAR Distribution



Height of 39" / 100CM PAR Distribution

